

## 1310nm 1500mW Multimode Laser Diode

Part Number		WSLD-1310-1500m-3		
PARAMETER		SYMBOL	VALUE	UNIT OF MEASURE
Reverse Voltage		V <sub>r</sub>	2.0	V
Operating Temperature		T <sub>op</sub>	+10~+30	°C
Storage Temperature		T <sub>stg</sub>	-20~+80	°C
Lead Soldering Temperature (10 sec.)		T <sub>is</sub>	260	°C
Typical Specification (@25°C)		Min.	Typical Value	Max.
Optical Parameters	Center Wavelength	1310nm +/-30nm		
	Output Power	----	1.5W	----
	Spectral Width(FWHM)	----	7.0nm	----
	Wavelength Temp. Coefficient	0.7nm/°C		
	Laser Type	FP		
	Beam Type	Multimode		
	Emitter Size	85um x 1um		
	Beam Divergence (FWHM)	----	28° ±x8° //	----
	Slope Efficiency	----	0.5W/A	----
Electrical Parameters	Threshold Current	----	0.4A	0.7A
	Operating Current	----	3.3A	3.5A
	Operating Voltage	----	1.3V	1.5V
Photodiode Parameters	Photodiode	Without		
	PD Current	----	----	----
	PD Reverse Voltage (Max. )	----		
Other Parameters	Package	TO3		
	Recommended Operating Temp.	25°C		

**Product Package View:**
**TO3 Package:**
