

### 1310nm 1500mW Multimode Laser Diode

Part Number		WSLD-1310-1500m-H		
PARAMETER	SYMBOL	VALUE	UNIT OF MEASURE	
Reverse Voltage	$V_r$	2.0	V	
Operating Temperature	$T_{op}$	+10~+30	°C	
Storage Temperature	$T_{stg}$	-20~+80	°C	
Lead Soldering Temperature (10 sec.)	$T_{is}$	260	°C	
Typical Specification (@25°C)		Min.	Typical Value	Max.
Optical Parameters	Center Wavelength	1310nm+/-30nm		
	Output Power	----	1.5W	----
	Spectral Width(FWHM)	----	7.0nm	----
	Wavelength Temp. Coefficient	0.7nm/°C		
	Laser Type	FP		
	Beam Type	Multimode		
	Emitter Size	85um x 1um		
	Beam Divergence (FWHM)	----	28° $\perp$ x8°//	----
Electrical Parameters	Threshold Current	----	0.4A	0.7A
	Operating Current	----	3.3A	3.5A
	Operating Voltage	----	1.3V	1.5V
Photodiode Parameters	Photodiode	Without		
	PD Current	----	----	----
	PD Reverse Voltage (Max. )	----		
Other Parameters	Package	H-mount		
	Recommended Operating Temp.	25°C		

**Product Package View:**

**H-mount Package:**

