

### 980nm 5W Multimode Laser Diode

Part Number		WSLD-980-005-C		
PARAMETER	SYMBOL	VALUE	UNIT OF MEASURE	
Reverse Voltage	$V_r$	2.0	V	
Operating Temperature	$T_{op}$	+10~+30	°C	
Storage Temperature	$T_{stg}$	-20~+80	°C	
Lead Soldering Temperature (10 sec.)	$T_{is}$	260	°C	
Typical Specification (@25°C)		Min.	Typical Value	Max.
Optical Parameters	Center Wavelength	976nm+/-10nm		
	Output Power	----	5.0W	----
	Spectral Width(FWHM)	----	3.0nm	----
	Wavelength Temp. Coefficient	0.35nm/°C		
	Laser Type	FP		
	Beam Type	Multimode		
	Emitter Size	100um x 1um		
	Beam Divergence (FWHM)	----	35° $\perp$ x8°//	----
Electrical Parameters	Slope Efficiency	----	1.0W/A	----
	Threshold Current	----	0.3A	0.7A
	Operating Current	----	5.2A	5.5A
Photodiode Parameters	Operating Voltage	----	1.6V	2.2V
	Photodiode	Without		
	PD Current	----	----	----
Other Parameters	PD Reverse Voltage (Max. )	----		
	Package	C-mount		
	Recommended Operating Temp.	25°C		

**Product Package View:**

**C-mount Package:**

